

# 2000L LPE Extraction System

*PRODUCTION SERIES*

**PURE**<sup>5</sup>  
Powered by **COMERG**

## Extraction Vessel

- **Volume:** 4x500L vessel holds up to 200-300 pound of dried and ground material
- **Pressure:** Maximum system operating pressure 12 bar
- **Temperature:** max 85°C (185°F)
- **Power consumption [instaled]:** 300 kW
- **Materials:** 304 stainless steel
- **Vessel:** interior is polished to food grade level
- **Closures:** ASME flange, both ends
- **Sealing:** PTFE flat seals
- **Temperature measurement:** Pt100 sensors
- **Water Jacket volume:** 200 Liters (53 gallons)
- **Safety:** spring loaded safety relief valve
- **Raw material feeding:** vacuum mode
- **Residue removal:** vacuum mode, quick closure
- **Raw material agitation:** low speed stirrer

## Separator/Collection Vessel

- **Separator:** Jacketed separator/collection vessel
- **Volume:** 1 pieces x 150 Liters
- **Pressure:** Maximum system operating pressure 12 bar
- **Temperature:** max 85°C (185°F)
- **Materials:** 304 stainless steel
- **Cleaning:** manual by direct access
- **Safety:** spring loaded safety relief valve
- **Flow path:** from extractor to separator is continuous diameter with no constrictions

## Heat Exchanger

- **Construction:** Plate type and shell & tube type
- **Materials:** all 304 stainless steel
- **Cooling/Heating:** R134a refrigerant



## Chiller/Receiver

- **Refrigeration:** heat pumping
- **Temperature range:** 20°C to 45°C (68°F to 113°F)
- **Maximum solvent content:** 1000 kg

## Skid & Extractors Physical Dimensions

- **Skids number:** 2 pieces
- **Height:** 3,000 mm
- **Length:** 10,000 mm
- **Width:** 5,000 mm
- **Total weight:** app. 24,000 kg
- **Floor mounting area:** min. 120 m<sup>2</sup>
- **Ceiling height:** 5.5 m

## Control System

- **Functions:** Fully automatic Programmable Logic Controller (PLC) touch screen interface with first level safety functionality and user programmable pressure, temperature and time.
- **Safety:** pressure transducers monitor system pressure and shut down system to prevent accidental over-pressurization

For pricing information, a demo or more information contact:

**Email:** [info@comerg.com](mailto:info@comerg.com)

**Tel:** 602-992-0744

**Web:** [www.comerg.com](http://www.comerg.com)