

Stick and Seed Separation

CUSTOM SERIES

PURE⁵
Powered by COMERG

Feeding Conveyor

- **Model:** 2.5m shaft
- **Motor power:** 3kW
- **Material:** food grade stainless steel
- **Screw material:** food grade stainless steel
- **Application:** conveying material to the sifter bay

Sifter

- **Width:** 2000mm
- **Length:** 4000mm
- **Motor power power:** 2.55kw
- **Frame material:** food grade stainless steel
- **Speed controller:** 1pieces

Separator

- **Model:** 12Mx4L
- **Fractions:** 3 fractions
- **Insulation layer:** rock wool 25mm
- **Sift material:** 304SS
- **Insulation layer:** Rock wool 25mm, sealing rubber strip.
- **Mesh:** SS 304 stainless
- **Chain:** P=25.4, Supporting roller, Supporting tube: $\varnothing 21.5$.
- **Transmission shaft:** $\varnothing 45$.
- **Bearing:** 6308
- **Frame:** 8#U steel, 80*40Galvanized square
- **Sealing device:** Rock wool insulation.
- **Discharge seal plate:** aluminium silicate board.
- **Drying temperature:** 0-90 degree centigrade, Can be adjusted.

Cydon

- **Size:** 3424*2182*1838 mm
- **Blower system:** 2.2kW
- **Temperature:** 0-90°C



Control cabinet

- **Model:** Frequency converter
Control the motor power of dryer
Control the speed of dryer
Control the temperature of dryer
- **Total power:** 27.75kW

Electric consumption

- **Total Power:** 22.2kW

For pricing information, a demo or more information contact:

Email: info@comerg.com

Tel: 602-992-0744

Web: www.comerg.com