

50L MAX LPE Extraction System

Product Spec

COMERG **PURE** 5

Powered by
 **COMERG**

Extraction Vessel

- **Volume:** 2x25L vessel holds up to 6-8 pounds dry material
- **Pressure:** Maximum system operating pressure 12 bar
- **Temperature:** max 45C (113F)
- **Materials:** 304 stainless steel
- **Vessel:** interior is polished to food grade level
- **Closures:** ASME flange
- **Sealing:** Flanges with PTFE flat seals
- **Temperature measurement:** Pt100 sensors
- **Water Jacket volume:** 15 Liters (4 gallons)
- **Safety:** spring loaded safety relief valve
- **Raw material feed:** top loading
- **Residue removal:** flange closure, manual

Separator/Collection Vessel

- **Separator:** Jacketed separator/collection vessel
- **Volume:** 40 Liters (106gallons)
- **Pressure:** Maximum operating pressure 12 bar
- **Temperature:** max 60C (140F)
- **Materials:** 304 stainless steel
- **Safety:** spring loaded safety relief valve
- **Flow path:** continuous with no constrictions

Heat Exchanger

- **Construction:** refrigeration unit
- **Materials:** all 304 stainless steel
- **Cooling/Heating:** R404a refrigerant

Chiller/Receiver

- **Refrigeration:** heat pumping
- **Temperature range:** -10C to SOC (14F to 158F)
- **Maximum solvent content:** 65 kg



Skid Physical Dimensions

- **Height:** 1,550 mm
- **Length:** 1,750 mm
- **Depth:** 800 mm
- **Total weight:** app. 1,000 kg
- **Floor mounting area:** min. 10 m²
- **Ceiling height:** 2.5 m

Control System

- **Functions:** Fully Automatic Programmable PLC, touch screen interface with first level functionality and user programmable pressure, temperature and time.
- **Safety:** pressure transducers monitor system pressure and shut down system to prevent accidental over-pressurization.

For pricing information, a demo or more information contact:

Email: info@comerg.com

Tel: 602-992-0744

Web: www.comerg.com